

# Results

---

<b>To:</b> Edmond Gomes	<b>From:</b> Doug Gaunt
<b>Organisation:</b> IBS	<b>Subject:</b> 2400mm 12mm OSB Ergo with Handibracs– P21 test results.
<b>Location:</b> Auckland	<b>Date:</b> 1 August 2017
<b>Mob No.:</b>	<b>No. of</b> 5
<b>Tel No.:</b> 09 5740324	<b>Pages:</b>

---

Please call +64 7 343 5763 if transmission incomplete

Edmond

Please find below the results of your three 4 x 2.4m 12mm OS Ergo one side walls as tested with GIB Handibracs.

1. BU wind = 48 (20 BU/m) as limited by the ultimate load capacity.
2. BU Earthquake = 65 (27 BU/m) as limited by the ultimate load capacity.

Figures 1, 2 & 3 show the load deflection plots, Figure 4 shows the P21:2010 calculations.

## Wall Construction


- 90x45 SG10 H1.2 timber studs (600 centres), two rows of nogs
- 90x45 SG10 H1.2 timber top and double bottom plates
- Four 600mm wide sheets horizontally fixed 12 mm OSB Ergo board one Top & 3rd row down sheets joined on centre stud
- OSB fixed with 50x2.55 Jolt head Galv nails at 150mm centres
- GIB Handibrac brackets to ends on bottom plate
- Tested with M12 hold down bolts to GIB Handibrac brackets and bottom plate.

**RISK AND LIMITATION OF LIABILITY:** Scion's liability to the Client arising out of all claims for any loss or damage resulting from this work will not exceed in aggregate an amount equal to two times the Service Fees actually paid by the Client to Scion. Scion will not be liable in any event for loss of profits or any indirect, consequential or special loss or damage suffered or incurred by the Client as a result of any act or omission of Scion under this Agreement.

**USE OF NAME:** The Client will not use Scion's name in association with the sale and/or marketing of any goods or services

## CAUTION


The information contained in this facsimile is confidential and may be legally privileged. If the reader of this message is not the intended recipient, you are hereby notified that any use, dissemination, distribution or reproduction of this message is prohibited. If you have received this message in error, please notify us immediately and return the message to us by mail. Thank you.




**Figure 1: Wall 278019**

**Failure Mode**

- No damage to OSB Board or fastenings however horizontal sliding of OSB sheets along each other
- No bending of Handibracs brackets
- No damage to bottom plates
- No damage to other framing



**Figure 2: Wall 278020**



**Top of Wall Deflection, mm**


**Figure 3: Wall 278021**



P21:2010 BRACING RACKING TEST RESULT EVALUATION								
Wall Construction								
2400mm, Four 600mm wide sheets Horizontally fixed 12 mm OSB Ergo board,								
Top & 3rd row down Joined at centre stud								
Nailed 150 centres Round outside Studs & Plates using 50x2.55 Jolt head						Summary		
90x45 Red Stag SG10 top and Bottom plates and Studs - Two rows of no						Earthquake	27 (U)	BU/m
GIB Handie Brac Hold down bracks each end with M12 rods to Reaction						Wind	20 (U)	BU/m
Date of test:-	28-Jul-17	Ship No.	2960	Tested by		Doug Gaunt		
Date of calc's:-	1-Aug-17	Job No.	TE17-007	Analysed by		Doug Gaunt		
Calculated to BRANZ P21:2010, AS/NZS1170.2&5, NZS3604:2010 Scion, Private Bag 3020 Rotorua.								
Serviceability Cycles			Ultimate Cycles			Wall dimensions		
Lab Number	Direction	Cycle to H/300 or DLW	X mm	Cycle to Displacement	y=(mm)	L(mm)	H(mm)	
		Loads	Residual	Maximum		2400	2400	
		(P <sub>8</sub> )	Defln, C	Load	def @ P	d at P/2	4th,R	
		kN	mm	P(kN)	y (mm)	P/2 (kN)	d mm	kN
278019	+	3.00	3.20	3.88	22.0	1.94	2.5	3.25
	-	2.80	2.80	3.82	22.0			
278020	+	3.03	3.10	3.90	22.0	1.95	2.8	3.26
	-	3.30	2.20	4.05	22.0			
278021	+	3.48	4.50	3.91	22.0	1.96	1.4	3.00
	-	3.68	4.32	0.32	22.0			
Averages		(P <sub>8</sub> )	(C)	(P)	(y)	P/2 (kN)	(d)	(R <sub>y</sub> )
Averages		3.22	3.35	3.31	22.00	1.95	2.22	3.26
Coefficient of Variation %		9.39	24.27	40.46	0.00	0.32	28.19	4.22
y = average failure deflection or peak deflection of the three tests.								
d= average first cycle displacement at half peak, (the very first cycle wall reaches the load)								
R = Residual load, P = Peak Load, S = Serviceability load								
Displacement Recovery Factor (K1), (0.8 <= K1 <= 1.0)						Systems factor K2 = 1.2		
Average Structural Displacement Ductility factor						u = y/d 9.92		
Ductility Modification factor						K4 = 1.00		
DLW = Selected deflection limit for wind forces				DLQ = Selected deflection limit for earthquake forces				
P21:2010 BR Calc's		K1	EQ ultimate	EQ service	Wind Ultimate	Wind Service		
Lab Number	(BU)	(= 1.4 - C/X)	BU's	BU's	BU's	BU's		
278019	(BU)	1.00	64.8	126.5	77.0	98.0		
	(BU/m)		27	53	32	41		
278020	(BU)	1.00	66.6	138.1	79.5	107.0		
	(BU/m)		28	58	33	45		
278021	(BU)	0.85	64.2	132.6	42.3	102.7		
	(BU/m)		27	55	18	43		
<20% Result Check		278019	-1% Ok result	-7% Ok result	50.8	-7% Ok result		
		278020	3% Ok result	6% Ok result	50.8	6% Ok result		
		278021	-2% Ok result	0% Ok result	-85% Ok result	0% Ok result		
Note: Where the value of BR Wind or BR EQ for any specimen is more than 20% greater than either of the other two specimens, assign it a value of 1.2 times the lower value before averaging.								
Average Earthquake BR		Ultimate			Serviceability			
EQ (BU's)	20 x K4 x R <sub>y</sub> =	65	(P8 x K1) x (K2/0.55) =		132			
		27 BU/m	Limited by		Ultimate limit state			
Average Wind BR		Ultimate			Serviceability			
Wind (BU's)	20 * P =	48	(P8 x K1) x (K2/0.71) =		103			
		20 BU/m	Limited by		Ultimate limit state			

Figure 4: P21:2010 calculations for 2400mm x 2.4m, 12mm OSB Ergo, Handibracs

Please feel free to contact me to discuss this information.



Doug Gaunt